



TRIMITZTHANE GLOSS 580

Polyurethane Gloss

Product Description	A two components acrylic aliphatic polyurethane gloss finish coat.																											
Recommended Use	Polyurethane finish coat where attractive appearance and a wide range of protection is required.																											
Characteristics	<ul style="list-style-type: none"> Excellent gloss and colour retention. Outstanding weather resistance with excellent colour and gloss retention. Resistance to broad range of corrosive atmospheres. Excellent resistance to atmospheric exposure. Hard, tough and abrasion resistance. Good resistance to splash and spillage of acids, alkalies, salt solutions and aliphatic petroleum products. Can be recoated even after long atmospheric exposure. 																											
Physical Data	<table> <tr> <td>Colour</td><td>Available On Request</td></tr> <tr> <td>Gloss Level</td><td>Gloss</td></tr> <tr> <td>Volume Solid</td><td>Light Colour, approx. 49% Dark Colour, approx. 45%</td></tr> <tr> <td>Dry Film Thickness</td><td>40 - 60 microns per coat</td></tr> <tr> <td>Number of Coat</td><td>1 or 2</td></tr> <tr> <td>Theoretical Coverage</td><td>Light Colour, 9.80 m²/ltr for 50 μ Dark Colour, 9.00 m²/ltr for 50 μ</td></tr> <tr> <td>Temperature Resistance</td><td>Continuous : 93°C (dry) Intermittent : 121°C (dry)</td></tr> <tr> <td>VOC</td><td>230 g/ltr</td></tr> <tr> <td>Flash Point</td><td>Base : 29°C Hardener : 38°C</td></tr> <tr> <td>Shelf Life</td><td>At least 12 months</td></tr> <tr> <td>Pack Size</td><td> <table> <tr> <td>5 litres unit</td><td>Base : 4,375 litres, Hardener : 0,625 litre</td></tr> <tr> <td>20 litres unit</td><td>Base : 17.5 litres , Hardener : 2.5 litres</td></tr> </table> </td></tr> </table>		Colour	Available On Request	Gloss Level	Gloss	Volume Solid	Light Colour, approx. 49% Dark Colour, approx. 45%	Dry Film Thickness	40 - 60 microns per coat	Number of Coat	1 or 2	Theoretical Coverage	Light Colour, 9.80 m ² /ltr for 50 μ Dark Colour, 9.00 m ² /ltr for 50 μ	Temperature Resistance	Continuous : 93°C (dry) Intermittent : 121°C (dry)	VOC	230 g/ltr	Flash Point	Base : 29°C Hardener : 38°C	Shelf Life	At least 12 months	Pack Size	<table> <tr> <td>5 litres unit</td><td>Base : 4,375 litres, Hardener : 0,625 litre</td></tr> <tr> <td>20 litres unit</td><td>Base : 17.5 litres , Hardener : 2.5 litres</td></tr> </table>	5 litres unit	Base : 4,375 litres, Hardener : 0,625 litre	20 litres unit	Base : 17.5 litres , Hardener : 2.5 litres
Colour	Available On Request																											
Gloss Level	Gloss																											
Volume Solid	Light Colour, approx. 49% Dark Colour, approx. 45%																											
Dry Film Thickness	40 - 60 microns per coat																											
Number of Coat	1 or 2																											
Theoretical Coverage	Light Colour, 9.80 m ² /ltr for 50 μ Dark Colour, 9.00 m ² /ltr for 50 μ																											
Temperature Resistance	Continuous : 93°C (dry) Intermittent : 121°C (dry)																											
VOC	230 g/ltr																											
Flash Point	Base : 29°C Hardener : 38°C																											
Shelf Life	At least 12 months																											
Pack Size	<table> <tr> <td>5 litres unit</td><td>Base : 4,375 litres, Hardener : 0,625 litre</td></tr> <tr> <td>20 litres unit</td><td>Base : 17.5 litres , Hardener : 2.5 litres</td></tr> </table>	5 litres unit	Base : 4,375 litres, Hardener : 0,625 litre	20 litres unit	Base : 17.5 litres , Hardener : 2.5 litres																							
5 litres unit	Base : 4,375 litres, Hardener : 0,625 litre																											
20 litres unit	Base : 17.5 litres , Hardener : 2.5 litres																											
Surface Preparation	<p>Refer to specific instructions for primer and intermediate coats being used for application. All previous coats must be clean and dry.</p> <p>Old coating system must be roughened, cleaned and dry.</p>																											
Application Data	<table> <tr> <td>Application Methods</td><td></td></tr> <tr> <td>Airless Spray</td><td></td></tr> <tr> <td>Nozzle Tip</td><td>0.46 - 0.58 mm (0.018 - 0.023 inch)</td></tr> <tr> <td>Nozzle Pressure</td><td>10 MPa (approx. 1400 psi)</td></tr> <tr> <td>Conventional Spray</td><td></td></tr> <tr> <td>Nozzle Tip</td><td>1.8 - 2.0 mm (0.071 - 0.079 inch)</td></tr> <tr> <td>Nozzle Pressure</td><td>0.3 MPa (approx. 43 psi)</td></tr> <tr> <td colspan="2">Brush or Roller Recommended</td></tr> </table>		Application Methods		Airless Spray		Nozzle Tip	0.46 - 0.58 mm (0.018 - 0.023 inch)	Nozzle Pressure	10 MPa (approx. 1400 psi)	Conventional Spray		Nozzle Tip	1.8 - 2.0 mm (0.071 - 0.079 inch)	Nozzle Pressure	0.3 MPa (approx. 43 psi)	Brush or Roller Recommended											
Application Methods																												
Airless Spray																												
Nozzle Tip	0.46 - 0.58 mm (0.018 - 0.023 inch)																											
Nozzle Pressure	10 MPa (approx. 1400 psi)																											
Conventional Spray																												
Nozzle Tip	1.8 - 2.0 mm (0.071 - 0.079 inch)																											
Nozzle Pressure	0.3 MPa (approx. 43 psi)																											
Brush or Roller Recommended																												



TRIMITZTHANE GLOSS 580

Polyurethane Gloss

Mixing Ratio By Volume	Base : Hardener = 7 : 1
Thinner	Thinner Trimitz 910
Cleaner	Thinner Trimitz 930
Surface Temperature	Should be 10°C - 49°C, at least 3°C above the dew point to prevent condensation
Drying Time	
Touch Dry	1 hour at 25°C, 30 minutes at 32°C
Trough Dry	7 hours at 25°C, 4 hours at 32°C
Overcoating	
Minimum	4 hours at 25°C, 2 hours at 32°C
Maximum	Unlimited
Full Cure	7 days
Pot Life	18 hours at 25°C, 8 hours at 32°C

System Compatibility	Primer <ul style="list-style-type: none"> • Trimitzpoxy primer 471 • Trimitzpoxy MP 485 • Trimitztic 480 • Trimitz Etch <p>For other suitable primers or intermediates, please consult Trimitz Protective Coating.</p>
-----------------------------	---

Safety Precaution	<p>Keep away from heat, spark and open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use.</p> <p>Proper ventilation and protective measures must be provided during mixing, application and drying, to keep vapour concentration within safe limits and to protect against toxic hazard.</p> <p>Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.</p>
--------------------------	---

Disclaimer	<p>The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.</p>
-------------------	---